

# Hammer drills – exceptional performance

**Power through  
concrete + stone**

BH 16 V



BH 21



- Impressive drilling and hammering performance
- Durable and simple design
- Exceptional versatility – perfect for use in mining, construction, quarrying and industrial applications
- From model BH11 available with power blowing system for blowing out the drill hole

	Model	Blow frequency per min	Air demand *) m³/min	Chuck – Shank		Weight kg	Impact energy Joules	Weighted sum acceleration value **) m/s²
Grip	BH 8	3660	0.5	S 19 x 82,5	a)	8.6	8.5	15.4
	BH 8	3660	0.5	S 22 x 82,5	a)	8.6	8.5	15.4
	BH 11	2910	1.1	S 22 x 108	b)	15.5	19.0	22.0
T-grip	BH 16	2400	1.6	S 22 x 108	b)	18.9	30.0	19.0
	BH 21	2740	2.1	S 22 x 108	b)	24.4	40.0	17.7
T-grip Vibration damped	BH 16 V	2440	1.6	S 22 x 108	b)	22.9	30.0	10.6

\*) At 5 bar    \*\*) As per ISO28927-10, measured at 5 bar    a) = Retaining spring b) = Retaining catch  
Appropriate bits are separately available: Monoblock bit, cone drill rod, core bit

**Hose lubricator (1.4!):**

Recommended accessory for compressors without tool lubricators, or for compressors with integrated tool lubricator if the distance to the tool exceeds 20m, or if there is a height difference to the tool.



**KAESER KOMPRESSOREN SE**

P.O. Box 2143 – 96410 Coburg – GERMANY – Tel +49 9561 640-0 – Fax +49 9561 640130  
e-mail: productinfo@kaeser.com – www.kaeser.com